

Diamond Coil



PRE-FORMED

Windings

Tel +44 (0) 114 248 4391 Fax +44 (0) 114 247 7663
Email pfsales@preformed.co.uk

Customer:

Contact:

Telephone:

Date:

Motor Manufacturer:

Serial No.:

Frame No.:

Machine Voltage:

Machine Amps:

Frequency:

HP/ KW/ KVA:

Revs per Minute:

Insulation Class:

Hardcoil: Softcoil: Other:

| | |
|----|---|
| 1 | Core inside Diameter: |
| 2 | Core Length: |
| 3 | Finger Plate Width: |
| 4 | Number of Slots: |
| 5 | Number of Coils: |
| 6 | Total Slot Depth: |
| 7 | Coil Space under Wedges: |
| 8 | Slot Width: |
| 9 | Slot Skew Left Distance: |
| 10 | Slot Skew Right Distance: |
| 11 | Turns per Coil: |
| 12 | Conductor Size - Width: Thickness: |
| 13 | No. of Conductors in Parallel: |
| 14 | Coil Pitch 1- |
| 15 | Weight of Insulated Coil: |
| 16 | Connection End Coil Projection: |
| 17 | Back End Coil Projection: |

| | |
|----|---|
| 18 | Overall Coil Length: |
| 19 | Coil Slot Length Top Leg: |
| 20 | Coil Slot Length Bottom Leg: |
| 21 | Bracing Ring Distance from Core Connection End: |
| 22 | Distance from Core Back End: |
| 23 | Internal Diameter Connection End: |
| 24 | Internal Diameter Back End: |
| 25 | Lead Position: |
| 26 | Lead Position: |
| 27 | Wound Tops Left: |
| 28 | Wound Tops Right: |
| 29 | Core to Top of Coil Connection End: |
| 30 | Core to Bottom of Coil Connection End: |
| 31 | Core to Top of Coil Back End: |
| 32 | Core to Bottom of Coil Back End: |
| 33 | Please Tick: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> other <input type="checkbox"/> |

